



Product Features

- wetted parts made of stainless steel
- maintenance-free spindle gasket with self-lubricating EPDM lip gasket
- EPDM-seat gasket
- press connection Geberit MAPRESS
- with sidewise drain valve, rotatable hose connection element G 3/4
- with test port
- check valve with SST spring
- wear-resistant stainless steel valve seat
- with a black handwheel
- free from dead spots
- for any installation position
- Open position indicator

Standards and Approvals

- according to DVGW regulations
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- acc. to DIN EN 13959 provisions
- ÚA-Reg.-Nr. R-15.2.3-21-17049, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

Part no.	DN	A1 (mm)	A2	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	T1 (mm)	Z1 (mm)	Z2 (mm)	Z3 (mm)	Zeta	$\Delta p_{\text{opening}}$ (hpa)	cv (m ³ /h)
0600101500	15	15	G 1/4	60	100	20	112	20	22	50	72	4.9	120	4.03
0600102000	20	22	G 1/4	60	120	21.5	125	21	26	57	83	3.6	110	8.3
0600102500	25	28	G 1/4	70	140	25	146	23	35.5	64.5	100	2.9	130	14.6
0600103200	32	35	G 1/4	70	165	26.5	167	26	34	80.5	115.5	2.6	80	25.3
0600104000	40	42	G 1/4	90	190	30	189	30	36	93	129	3.1	80	35.9
0600105000	50	54	G 1/4	90	230	35.5	222	35	41	111	152	2.3	70	64.7

Part no.	kg
0600101500	0.51
0600102000	0.69
0600102500	1.01
0600103200	1.43
0600104000	2.13
0600105000	3.08

Accessories

- SST sampling valve, figure 087 00
- insulation shell for inclined stop valves, figure 471 10

Spare parts

- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- stainless steel head part for combined stop and check valves, shut off bonnet with check valve, figure E0120 060 00