



Product Features

- wetted parts made of stainless steel
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- male union thread
- without drain port (drain valve cannot be added)
- spindle thread not in contact with medium
- wear-resistant stainless steel valve seat
- with a black handwheel
- free from dead spots
- Open position indicator

Standards and Approvals

- DVGW approval
- ÖVGW approval
- SVGW approval
- WRAS approval
- KIWA approval
- VA approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17049, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 110 °C

| Part no. | DN | A1 | D1 (mm) | H1 (mm) | H2 (mm) | L1 (mm) | Zeta | cv (m ³ /h) | kg |
|------------|----|---------|---------|---------|---------|---------|------|------------------------|------|
| 0730G01500 | 15 | G 3/4 | 60 | 100 | 17.5 | 70 | 2.3 | 5.9 | 0.39 |
| 0730G02000 | 20 | G 1 | 60 | 100 | 19 | 78.5 | 1.6 | 12.5 | 0.54 |
| 0730G02500 | 25 | G 1 1/4 | 70 | 128 | 21 | 97 | 1.4 | 21.3 | 0.9 |
| 0730G03200 | 32 | G 1 1/2 | 70 | 145 | 24 | 110 | 1.1 | 38.7 | 1.16 |
| 0730G04000 | 40 | G 1 3/4 | 70 | 153 | 28 | 130 | 1.8 | 47.2 | 1.71 |
| 0730G05000 | 50 | G 2 3/8 | 90 | 195 | 33 | 145 | 1.4 | 84.8 | 2.59 |

Accessories

- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, FPT, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- insulation shell for inclined stop valves, figure 471 10

Spare parts

- EPDM seat gasket, figure B9100 173 08
- Head part gasket, figure C3100 173 07
- spindle seal as self-lubricating EPDM lip gasket for valves, figure C9100 173 03
- stainless steel shut off bonnet, figure E0120 073 02
- handwheel, figure G0100
- Installation sleeve for replacement of spindle seal, figure M9100 173 00
- handwheel set, figure 999 00