



## Product Features

- cover made of EPP
- Connection to the pipe by enclosed flex pipe (500mm)
- control of external immersion and metering pump possible
- readout of data, for example operating status, possible using USB interface
- operating times can be defined
- easy operation using touch screen
- Connection to power supply with type F safety plug
- Increase in discharge capacity possible through parallel operation
- frost protection monitor
- low-noise operation
- high performance
- plastic drain connection according EN 1717
- wetted parts on the drinking water side made of gunmetal, stainless steel and drinking water approved plastics
- with coupling nut for flat sealing connection thread including EPDM gasket
- Non-drinking water can be integrated (optional)
- View operating and system data conveniently via BMS connection
- normally closed inlet valve
- drain overflow monitoring (optional)
- for the protection of drinking water against non-potable water of fluid category 5 in accordance with DIN EN 1717/DIN 1988-100
- for wall mounting or installation on optional rack
- Energy-efficient and speed-modulating pump
- Flushing the PWC line up to 3 times a day
- Cleaning of the storage container (optional) possible
- maintenance requirements in accordance with DIN EN 806-5 must be complied with
- For more information on parallel operation, please contact your sales representative
- additional country-specific versions on request
- Spare parts on request

## Standards and Approvals

- DIN 3546-1

## Technical data

- pressure rating PN 10
- max. operating temperature 35 °C
- min. ambient temperature 2 °C
- max. ambient temperature 40 °C
- protection class IPX4
- power supply 230 V AC
- volume of receiver tank 30 l
- Flushing volume of PWC line 10 l/min (at 3 bar)
- power factor 0.98

Part no.	DN	max. head (m)	max. flow rate (m <sup>3</sup> /h)	A1	A2	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	T1 (mm)	T2 (mm)
3693002500	25	44	3.6	G 1 1/4	G 1 1/4	75	1038	930	600	110	94	206	330	215

Part no.	T3 (mm)	T4 (mm)	minimum flow pressure (MPa)	nominal connection diameter, waste water (mm)	flow limiter in inlet	kg
3693002500	147.6	9.5	0.15	75	70	50.00

### Accessories

- Y-strainer, figure 602 00
- FK-5 and FK-5 PRO tank cleaning unit, figure 369 02
- FK-5 and FK-5 PRO rack, figure 369 03
- FK-5 and FK-5 PRO overflow sensor, figure 369 04

### Spare parts

- solenoid valve for FK-5 DN 20 and DN 25, figure 369 13 001
- TMC24A actuator for FK-5 DN 20 and DN 25, figure 369 16 001