



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- stainless steel cone
- plastic shaft can be shortened
- inlet female pipe thread, outlet male pipe thread with stabilizing path
- free from dead spots
- with isolating, balancing and pre-setting function

Standards and Approvals

- DVGW approval
- SVGW approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- inside micrometer 110 mm
- max. installation depth 110 mm
- pressure rating PN 16
- max. operating temperature 100 °C

Part no.	DN	A1	A2	D1 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	SW1 (mm)	T1 (mm)	Zeta	cv (m ³ /h)	kg
5630202000	20	Rp 3/4	R 3/4	38.5	110	35	45	135	17	16.3	6.9	6	0.67

Accessories

- insulation shell for UP-PLUS and ETA-THERM valves, figure 471 14
- handle for flush-mounted valves, figure 590 00
- operating cover for flush-mounted valves, figure 591 00
- fixing set UP-PLUS, figure 597 00
- UP-PLUS extension set, figure 599 00
- tubular box spanner, size 17/18, 550 mm, figure B5120 500 00

Spare parts

- plastic shaft for UP-PLUS flush-mounted valves and UP-PLUS extension set, figure L0100 560 00
- control spindle for flush-mounted valves UP-PLUS, figure P0100 560 00