



Product Features

- active monitoring system with alarm signal to protect against water damage by reliable detection of leakage in water distribution systems by means of water sensors
- consisting of control unit, water sensor and loaded KHS isolating valve PLUS with spring return actuator 230V, figure 686 05
- low pressure loss
- soft close stop valve to avoid water hammer
- for new build and retrofit
- with the functional options: leakage monitoring and timed-controlled protection, leakage monitoring and time-controlled flushing of the drinking water system, protection without leakage monitoring
- leakage control system with integrated timer, for the connection of up to two reporting lines with maximum 25 water sensors, as well as for the connection of max. 10 parallel-operated maximum flow isolating ball valves
- with detachable visual and / or acoustic error signal
- max. 16 programmable events
- display with background light

Standards and Approvals

- valve(s) with DVGW approval
- according to DVGW worksheet W 570
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 13828
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- min. ambient temperature 0 °C
- max. ambient temperature 50 °C
- protection class IP54
- power supply 230 V AC
- switching capacity 230 V, 2 A
- floating alarm relay, max. 230 V, 2 A
- own consumption 3 W
- wire cross section 3 x 0.75 mm²
- power input during actuation 4,5 W / 7 VA
- power input during standstill 3,5 W

Part no.	DN	A1	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	T1 (mm)	T2 (mm)	T3 (mm)
6200101500	15	G 3/4	3	4	79	30	22	160	46	13	3	58	44.5	8
6200102000	20	G 1	3	4	79	30	22	160	46	13	3	58	44.5	8
6200102500	25	G 1 1/4	3	4	79	30	22	160	46	13	3	58	44.5	8
6200103200	32	G 1 1/2	3	4	79	30	22	160	46	13	3	58	44.5	8

Part no.	kg
6200101500	2.77
6200102000	2.82
6200102500	2.94
6200103200	3.24

Accessories

- KHS quarter turn stop valve PLUS, 230 V spring return actuator, figure 686 05
- KHS free drain with overflow sensor, figure 688 00
- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- insulation shell for quarter turn stop valves and CONTROL-PLUS sensors, figure 471 19
- water sensor, figure 620 00 001
- flow limiter, figure 697

Spare parts

- KHS quarter turn stop valve without servo drive, figure 686 0G
- spring return actuator 230V for KHS quarter turn stop valves, figure 686 00 007/008