



Product Features

- for use exclusively in single and two-family houses
- prevents stagnation in ring pipe installations through forced flow during downstream withdrawals, can be used in cold drinking water (PWC)
- venturi technology creates parallel flow through main and loop pipe
- for flush mounted installation or in unaccessible locations
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- KHS Flow-Splitter pass with female thread
- plumbing unit feed pipe with female thread
- plumbing unit return pipe with female thread
- maintenance free
- free from dead spots
- KHS Flow-Splitter - static integrated into insulation shell of Neopor®
- suitable for horizontal and vertical installation

Standards and Approvals

- according to accepted materials list from German environmental agency
- CE marking
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 90 °C

Part no.	passage DN	Outlets DN	A1	A2	A3	H1 (mm)	H2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	T1 (mm)	kg
6405001500	15	15	Rp 1/2	Rp 1/2	Rp 1/2	48.5	110	210	185	100	40	0.59
6405002000	20	15	Rp 3/4	Rp 1/2	Rp 1/2	58.5	110	210	185	100	50	0.79