



### Product Features

- for temperature controlled operation of the KHS HS2® hygiene-flushing box
- to be connected to KHS HS2® hygiene-flushing box
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- male union thread
- free from dead spots

### Standards and Approvals

- according to accepted materials list from German environmental agency
- DIN EN 60751
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

### Technical data

- pressure rating PN 16
- max. operating temperature 105 °C
- length of connection cable 5 m

Part no.	DN	A1	A2	A3	H1 (mm)	L1 (mm)	L2 (mm)	kg
6890001500	15	G 3/4	G 3/4	G 1/4	65	65	60	0.49
6890002000	20	G 1	G 1	G 1/4	68	67	60	0.55
6890002500	25	G 1 1/4	G 1 1/4	G 1/4	70.5	72	70	0.7
6890003200	32	G 1 1/2	G 1 1/2	G 1/4	78	77	80	0.77
6890004000	40	G 1 3/4	G 1 3/4	G 1/4	79	82	80	0.87
6890005000	50	G 2 3/8	G 2 3/8	G 1/4	88.5	90	80	1.29

### Accessories

- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, FPT, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- insulation shell for MULTI T-PIECE, figure 471 28

### Spare parts

- threaded plug , figure J8101 173 00