



### Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- housing with G 2 coaxial thread for meter cartridges
- consisting of flush-mounted valve and water meter housing with plaster work protectors
- installation depth variable within the installation dimensions of the water meter
- for installation of a cold or hot-water metering cartridge
- as a one-piece cast water meter section
- maintenance-free EPDM spindle seal
- female pipe thread
- free from dead spots
- cast-on mounting feet with sound decoupling

### Standards and Approvals

- flush-mounted UP valve(s) DVGW approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- flush-mounted valve with soundproofing certificate according to DIN EN ISO 3822 Class 1
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

### Technical data

- inside micrometer 120 mm
- pressure rating PN 10
- max. operating temperature 70 °C
- short-term peak temperature 95 °C

Part no.	DN	A1	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	T1 (mm)	cv (m <sup>3</sup> /h)	kg
8554702000	20	Rp 3/4	105	75	31	24	234	120	44	140	64	16.3	4.1	1.59

### Accessories

- cap for stop valve water meter combinations and mounting blocks, figure 855 00 002
- RG120 grip top die-cast zinc set-up dimensions to 32 mm, figure 596 11
- RG120 grip top die-cast zinc set-up dimensions 30 mm to 110 mm, figure 596 12
- RG120 change stopper including extension for set-up dimensions to 110 mm, figure 596 15
- RG120 grip top plastic set-up dimensions up to 32 mm, figure 596 16
- RG120 grip-top plastic, set-up dimensions 30 mm to 110 mm, figure 596 17

### Spare parts

- RG120 inner top part, figure E0109 854 00 020