




### Product Features

- suitable for e.g. figure 173, 183 and 190
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- DN 65 and DN 80 for valves from 1991



### Standards and Approvals

- according to accepted materials list from German environmental agency
- for valves acc. DIN 3502

Part no.	DN	for DN	A1	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	H2 (mm)	kg
E010917302015KP	15	15	G 1/2	60	26.4	16.4	100	20	0.18
E010917302020KP	20	20	G 3/4	60	32.4	22	101.5	26.5	0.20
E010917302025KP	25	25	G 1	70	39.9	28	128.5	27	0.35
E010117302040KP	40	40	G 1 1/2	70	57.9	41.5	158	41	0.55
E010917302032KP	32	32	G 1 1/4	70	49.9	36	149	29	0.51
E010117302050KP	50	50	G 2	90	69.9	53	182.5	43	0.86
E010117302065KP	65	65	G 2 1/2	120	87.9	68	255	35.5	1.63
E010117302080KP	80	80	G 3	120	101.9	81	256	37	1.96