



Product Features

- configuration:
 - frost-proof outdoor valve
 - socket combination 2 x 230 V
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- lockable, stainless steel, polished surface
- as supply unit to the central power and water supply
- frame with door with profile cylinder lock as a key lock including bit keys
- retrofittable and interchangeable on an existing locking system
- can be converted on site to CH-KABA lock design
- door with integrated flap version for hose or cable connection for security even during operation
- maintenance-free EPDM spindle seal
- cone with internal CV spring
- can be extended to any length at construction site
- with aerator for automatic drainage
- integrated CV and tube aerator as a security combination HD
- male pipe thread
- actuating grip with blue identification plate
- free from dead spots
- incl. hose coupling for common connection systems
- lock with uniform key number on request, other configurations on request

Standards and Approvals

- valve with DVGW approval
- Valve with ÖVGW approval
- valve with SVGW approval
- Valve with KIWA approval
- Valve with BELGAQUA approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 15096 family H, type B / EN 1717 / DIN EN 13959

Technical data

- pressure rating PN 16
- protection class IP44

| Part no. | DN | A1 | A2 | D1 (mm) | H1 (mm) | H2 (mm) | H3 (mm) | H4 (mm) | H5 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | T1 (mm) | T2 (mm) |
|------------|----|-------|-------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 2130201500 | 15 | R 1/2 | G 3/4 | 35 | 510 | 282.5 | 160 | 114 | 25 | 288 | 198 | 91 | 132 | 56 |

| Part no. | flow at 0.05 Mpa (l/s) | flow at 0.1 MPa (l/s) | flow at 0.15 Mpa (l/s) | kg |
|------------|------------------------|-----------------------|------------------------|-------|
| 2130201500 | 0.4 | 0.67 | 0.8 | 10.57 |

Spare parts

- TRESOR mounting plate for sockets, figure E2120 210 03
- TRESOR lock with uniform key number, figure 210 99 003
- TRESOR lock, figure 210 99 002
- operating cap, figure 590 03 001
- hose coupling for Wall-Cabinets TRESOR, figure G3101 210 07
- TRESOR lock cylinder case, figure 210 98 001