



### Product Features

- low pressure loss
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- full bore
- female pipe thread
- removable inner top part TOP-ENTRY, with EPDM gasket body and gunmetal ball
- operating handle 90° rotatable
- free from dead spots

### Standards and Approvals

- DVGW approval
- WRAS approval
- KIWA UK water regulation 4 approval
- plastic parts with KTW and W 270 approval
- according to DVGW worksheet W 570
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 13828
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

### Technical data

- pressure rating PN 16
- max. operating temperature 90 °C

| Part no.   | DN | A1     | BS (mm) | D1 (mm) | H1 (mm) | H2 (mm) | L1 (mm) | T1 (mm) | HS (mm) | LS (mm) | kg   |
|------------|----|--------|---------|---------|---------|---------|---------|---------|---------|---------|------|
| 3850001500 | 15 | Rp 1/2 | 90      | 90      | 55.5    | 25      | 84      | 14.5    | 80.5    | 91      | 0.5  |
| 3850002000 | 20 | Rp 3/4 | 90      | 90      | 55.5    | 25      | 90      | 16.5    | 80.5    | 91      | 0.59 |
| 3850002500 | 25 | Rp 1   | 90      | 90      | 58.5    | 28      | 99      | 18      | 86.5    | 99      | 0.83 |

### Accessories

- insulation shell for quarter turn stop valves and CONTROL-PLUS sensors, figure 471 19

### Spare parts

- inner top part TOP ENTRY, for quarter turn stop valve and UP quarter turn stop valve for flush-mounted installation, figure E0109 386 00
- handle for quarter turn stop valve, figure 385 00 001