



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water

Standards and Approvals

- according to accepted materials list from German environmental agency
- similar to DIN 2566
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical data

- pressure rating PN 16
- max. operating temperature 200 °C

Part no.	DN	hole pattern (PN)	bolt holes	A1	D1 (mm)	D2 (mm)	D3 (mm)	D4 (mm)	L1 (mm)	S1 (mm)	kg
4260001500	15	10/16	4	Rp 1/2	95	65	45	14	20	14	0.68
4260002000	20	10/16	4	Rp 3/4	105	75	58	14	24	16	0.98
4260002500	25	10/16	4	Rp 1	115	85	68	14	24	16	1.2
4260003200	32	10/16	4	Rp 1 1/4	140	100	77	18	26	16	1.6
4260004000	40	10/16	4	Rp 1 1/2	150	110	88	18	26	16	1.81
4260005000	50	10/16	4	Rp 2	165	125	100	18	28	18	2.49
4260006500	65	10/16	4	Rp 2 1/2	185	145	122	18	32.5	18	3.33
4260008000	80	10/16	8	Rp 3	200	160	138	18	34	20	4.12
4260010000	100	10/16	8	Rp 4	220	180	159	18	38	20	4.76