



Product Features

- pre-assembled
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- suitable for fast subsequent installation on already finished outer wall
- inner top part for quick opening operation (two turns)
- high discharge capacity of 40 l / min (1 bar)
- EPDM-seat gasket
- can be extended to any length at construction site
- inlet male pipe thread
- free from dead spots
- incl. hose coupling for common connection systems
- flexible installation length with sliding wall disc in outdoor area
- matt chrome-plated handle with over-twist protection
- with theft-proof socket key operated
- with theft-proof aerator for automatic drainage
- discharge body with mounting surfaces

Standards and Approvals

- WRAS approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- soundproofing certification according to DIN EN ISO 3822 Class 1
- EN 1717

Technical data

- min. installation depth 150 mm
- pressure rating PN 16
- max. operating temperature 65 °C

Part no.	DN	A1	A2	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)
5791101500	15	R 1/2	G 3/4	35	15	71.5	114	100	363	242	122	61.5	495	253.5

Part no.	T1 (mm)	flow at 0.05 Mpa (l/s)	flow at 0.1 MPa (l/s)	flow at 0.15 Mpa (l/s)	kg
5791101500	56	0.46	0.67	0.82	1.44

Accessories

- FROSTI collar XL, figure 577 12 015
- FROSTI® lockable handle, figure 578 00 003
- FROSTI® lockable handle, for uniform key, figure 578 02 003

Spare parts

- FROSTI® socket key operated head part with socket key, figure 578 00 001
- FROSTI® socket key, figure 578 00 004
- FROSTI® spindle XL with cone without CV, figure 578 34 001