



## Product Features

- to control, log and monitor water exchange measures in PWC and PWH installations
- as an expansion module for the KHS mini control system MASTER 2.0/2.1
- expandable by 62 units in the CAN-bus in the MASTER/SLAVE system
- For connection of max. one of each of the following: KHS quarter turn stop valve or KHS quarter turn stop valve PLUS or CoolFlow cold water balancing valve, KHS temperature sensor Pt1000, KHS CONTROL-PLUS and KHS overflow sensor
- Modes of operation: Time, temperature, volume flow and routine control
- settings will be adopted by KHS MASTER 2.0/2.1 via CAN bus cable
- for wall installation
- Operating modes (16 memory locations): Time, temperature, volume flow, routine control, security/leak protection and data logging
- In the case of direct connection of quarter turn stop valves PLUS or CoolFlow cold water balancing valves only the 230 Volt versions are compatible
- please commission and maintain according to the operating instructions at the construction site or optionally order these

## Technical data

- min. ambient temperature 0 °C
- max. ambient temperature 50 °C
- protection class IP54
- power supply 230 V AC
- external input 230 V
- switching capacity 230 V, 2 A
- floating alarm relay, max. 230 V, 2 A
- own consumption 3 W

Part no.	H1 (mm)	L1 (mm)	T1 (mm)	kg
6860200600	120	200	58	0.61

## Accessories

- CONTROL-PLUS flow and temperature sensor, Hz signal, union thread, figure 138 4G
- KHS quarter turn stop valve, with 230 V actuator, figure 686 04
- KHS quarter turn stop valve PLUS, 230 V spring return actuator, figure 686 05
- KHS temperature sensor Pt 1000, figure 628 0G
- KHS free drain with overflow sensor, figure 688 00
- KHS Flush Point, 230 V, figure 684 04
- KHS Flush Point, 230 V, with CONTROL-PLUS, figure 684 05
- KHS CoolFlow cold water balancing valve, with 230 V actuator, figure 615 0G