



### Product Features

- for temperature controlled operation of the KHS HS2<sup>®</sup> hygiene-flushing box
- to be connected to KHS HS2<sup>®</sup> hygiene-flushing box
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- male union thread
- free from dead spots

### Standards and Approvals

- according to accepted materials list from German environmental agency
- DIN EN 60751
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

### Technical data

- pressure rating PN 16
- max. operating temperature 105 °C
- length of connection cable 5 m

| Part no.   | DN | A1      | A2      | A3    | H1 (mm) | L1 (mm) | L2 (mm) | kg   |
|------------|----|---------|---------|-------|---------|---------|---------|------|
| 6890001500 | 15 | G 3/4   | G 3/4   | G 1/4 | 65      | 65      | 60      | 0.49 |
| 6890002000 | 20 | G 1     | G 1     | G 1/4 | 68      | 67      | 60      | 0.55 |
| 6890002500 | 25 | G 1 1/4 | G 1 1/4 | G 1/4 | 70.5    | 72      | 70      | 0.7  |
| 6890003200 | 32 | G 1 1/2 | G 1 1/2 | G 1/4 | 78      | 77      | 80      | 0.77 |
| 6890004000 | 40 | G 1 3/4 | G 1 3/4 | G 1/4 | 79      | 82      | 80      | 0.87 |
| 6890005000 | 50 | G 2 3/8 | G 2 3/8 | G 1/4 | 88.5    | 90      | 80      | 1.29 |

### Accessories

- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, FPT, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- insulation shell for MULTI T-PIECE, figure 471 28

### Spare parts

- threaded plug , figure J8101 173 00