



### Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- suitable for access door installation or flush mounted installation
- maintenance-free EPDM spindle seal
- EPDM-seat gasket
- stainless steel cone
- inlet female thread, output coupling nut
- gunmetal inner top part
- handle with blue or red dot for identification
- free from dead spots

### Standards and Approvals

- DVGW approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

### Technical data

- pressure rating PN 16
- max. operating temperature 100 °C

| Part no.   | DN | A1     | A2    | H1 (mm) | H2 (mm) | H3 (mm) | L1 (mm) | T1 (mm) | Zeta | cv (m <sup>3</sup> /h) | kg   |
|------------|----|--------|-------|---------|---------|---------|---------|---------|------|------------------------|------|
| 8600502000 | 20 | Rp 3/4 | G 3/4 | 98.5    | 75      | 45      | 46      | 16.3    | 6.8  | 6.1                    | 0.44 |

### Accessories

- tubular box spanner, size 17/18, 550 mm, figure B5120 500 00

### Spare parts

- operating cap, figure 590 03 001